

SINGLE-SIDED ADHESIVE TAPE FOR MEMBRANE OVERLAPPINGS OR CONTINUOUS JOINTS FOR OUTDOOR USE



- 4-layer single-sided acrylic tape with separation film
- Resistant to heat and cold
- Sealing meets the airtightness requirements of DIN 4108/7 standard "airtightness of buildings"

PROPERTY	STANDARD	U/M	VALUE
Total thickness	DIN EN 1942	mm	0,28
Adhesiveness	DIN EN 1939	N/25 mm	>35
Thermal resistance	–	°C	-40/+100
Working temperature	–	°C	>+5
UV resistance	–	months	4
Storage	–	°C	dry from +5/+25 and covered

DELIVERY VOLUME	
Code	D52145
Width	60 mm
Length	25 m
Pieces/package	24

Support	polyethylene film
Reinforcing layer	reinforcing PET grid
Separation layer	silicone paper
Glue	acrylate dispersion without solvents

APPLICATIONS

Ensures airtightness of overlapping junctions of synthetic or bituminous membrane. Borders and components prove to be airtight according to DIN 4108/7 standards.

APPLICATION TIPS

- Can be applied to smooth supports such as non-woven fabrics, wood, untreated OSB panels.
- We recommend the use of PRIMER for rough surfaces like rough OSB panels, concrete or masonry without plaster.
- The surfaces must be dry and free of dust and solvents such as grease or oil.